

QUALITY PURIFIES.



QUALITY WORKS.

LANXESS
Energizing Chemistry

New Lewabrane® Ultra Low Pressure (ULP) RO Membrane Elements

LANXESS expands its product portfolio of Lewabrane® RO membrane elements by ultra low pressure (ULP) types, which are specialized on the treatment of water with low salinity.

Key features

Lewabrane® ultra low pressure (ULP) membrane elements have a highly permeable polyamide membrane designed for applications where high productivity and moderate salt passage are important. The ULP membrane also offers high rejection of low molecular weight organics and critical compounds also known as “micro-pollutants.” The strength of the membrane is the near complete removal of these organic compounds at a low operational pressure.

Applications

The typical applications are the filtration of drinking water and wastewater. Drinking water and wastewater plants often process large quantities of raw water daily. A membrane with a higher flux or water permeability can process large quantities of water, hence it has a positive impact on operational costs due to its lower operational pressure. The higher permeability results in 40% lower pressure and therefore lower power consumption in comparison to the standard products.

Product name	Permeate flow	Salt rejection	Membrane area	Feed spacer thickness	Dimensions (L / Ø / ID / OD)
B085 ULP 4040	8.2 m ³ /day	99.5%	7.9 m ²	0.86 mm	1,016/100/19 mm (OD)
	2,150 gpd	99.5%	85 ft ²	34 mil	40/3.9/0.75 inch
B400 ULP ASD	38.6 m ³ /day	99.5%	37.2 m ²	0.86 mm (ASD spacer)	1,016/201/29 mm
	10,200 gpd	99.5%	400 ft ²	34 mil (ASD spacer)	40/7.9/1.125 inch
B440 ULP	42.6 m ³ /day	99.5%	40.9 m ²	0.7 mm	1,016/201/29 mm
	11,300 gpd	99.5%	440 ft ²	28 mil	40/7.9/1.125 inch

Elements are tested under the following conditions:
applied pressure 7.6 bar (110 psi), NaCl concentration 500 mg/l,
operating temperature 25 °C (77 °F), pH 7 and recovery rate 15%

X Lewabrane®

Although the ULP membrane has a high flux, its dense polyamide polymeric structure can reliably reject critical substances and salts to a high level. Thus, the typical application for this membrane is the production of drinking water.

It is widely known that troublesome contaminants should be removed at their source in order to avoid critical pollutants in water. Therefore, wastewater treatment is another important application for ULP membranes.




Figure 1: Improved permeability of ultra low pressure elements in comparison to standard brackish water and low energy elements.

Furthermore, **Lewabrane® B400 ULP ASD** elements have a tailor-made feed spacer based on alternating (thick-thin) strand design (ASD). The 34 mil feed spacer height offers a lower pressure drop compared to standard spacers, and also provides less bioaccumulation in the feed channel (by reduction of stagnant flow areas in the channel). During product development, several experiments were conducted to measure resistance to bio-growth. The data show a 40% longer operational time using the ASD spacer as compared to a standard spacer. This leads to lower operational costs from reduced usage of cleaning chemicals, and longer time between cleanings.

Conclusion

Lewabrane® B400 ULP ASD and its companion product, **Lewabrane® B440 ULP** (with a 10% larger membrane area) are highly recommended for low-salinity water applications. **Lewabrane® ULP** membrane elements offer the following key performance benefits:

- Extremely high flux
- Low operational costs
- Reliable performance due to ASD spacer

High process reliability

In order to reduce the typical organic fouling in wastewater, the ULP membrane is characterized by the highest hydrophilic surface of all **Lewabrane®** types. The hydrophilicity supports a thin protective water layer on the membrane surface, which reduces the adsorption of organics.

Contact

LANXESS Deutschland GmbH
Liquid Purification Technologies
Kennedyplatz 1
50569 Cologne, Germany
Phone: +49 221 88850
E-mail: lewabrane@lanxess.com

We will be happy to support your business. Please contact us for additional information: visit www.lpt.lanxess.com

LANXESS
Energizing Chemistry

Health and Safety Information: Appropriate literature has been assembled which provides information concerning the health and safety precautions that must be observed when handling the LANXESS products mentioned in this publication. For materials mentioned which are not LANXESS products, appropriate industrial hygiene and other safety precautions recommended by their manufacturers should be followed. Before working with any of these products, you must read and become familiar with the available information on their hazards, proper use and handling. This cannot be overemphasized. Information is available in several forms, e.g., material safety data sheets, product information and product labels. Consult your LANXESS representative in Germany or contact the Regulatory Affairs and Product Safety Department of LANXESS Deutschland GmbH or – for business in the USA – the LANXESS Corporation Product Safety and Regulatory Affairs Department in Pittsburgh, PA, USA.

Regulatory Compliance Information: Some of the end uses of the products described in this publication must comply with applicable regulations, such as the FDA, BIR, NSF, USDA, and CPSC. If you have any questions on the regulatory status of these products, contact – for business in the USA – the LANXESS Corporation Regulatory Affairs and Product Safety Department in Pittsburgh, PA, USA or for business outside US the Regulatory Affairs and Product Safety Department of LANXESS Deutschland GmbH in Germany. The manner in which you use and the purpose to which you put and utilize our products, technical assistance and information (whether verbal, written or by way of production evaluations), including any suggested formulations and recommendations are beyond our control. Therefore, it is imperative that you test our products, technical assistance and information to determine to your own satisfaction whether they are suitable for your intended uses and applications. This application-specific analysis must at least include testing to determine suitability from a technical as well as health, safety, and environmental standpoint. Such testing has not necessarily been done by us. Unless we otherwise agree in writing, all products are sold strictly pursuant to the terms of our standard conditions of sale. All information and technical assistance is given without warranty or guarantee and is subject to change without notice. It is expressly understood and agreed that you assume and hereby expressly release us from all liability, in tort, contract or otherwise, incurred in connection with the use of our products, technical assistance, and information. Any statement or recommendation not contained herein is unauthorized and shall not bind us. Nothing herein shall be construed as a recommendation to use any product in conflict with patents covering any material or its use. No license is implied or in fact granted under the claims of any patent.

All trademarks are trademarks of the LANXESS Group, unless otherwise specified. Status 07/2017.